



TEST REPORT

MODEL NAME : UP8S24WQ

1. DESIGN VERIFY TEST
 - 1-1. INPUT FUNCTION TEST
 - 1-2. OUTPUT FUNCTION TEST
 - 1-3. PROTECTION FUNCTION TEST
2. SAFETY TEST
3. RELIABILITY TEST

1. DESIGN VERIFY TEST

1-1. INPUT FUNCTION TEST

TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
VOLTAGE RANGE	90~277VAC	I/P: testing O/P:full load Ta:25 °C	test ok	P
FREQUENCY RANGE	47~63Hz no damage osc	I/P:90~277VAC O/P:full~min. load Ta:25 °C	test ok	P
EFFICIENCY	81% typ.	I/P:220VAC O/P:full load Ta:25 °C	81.11%	P
AC CURRENT	0.15A/115VAC typ. 0.1A/230VAC typ.	I/P:115VAC I/P:230VAC O/P:full load Ta:25 °C	0.15A/115VAC 0.09A/230VAC	P
INRUSH CURRENT	70A typ. cold start	I/P:230VAC O/P:full load Ta:25 °C	40A	P

1-2. OUTPUT FUNCTION TEST

TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
RIPPLE&NOISE	250mVp-p max.	I/P:115VAC I/P:230VAC O/P:full load Ta:25 °C	130mVp-p/115VAC 130mVp-p/230VAC	P
VOLTAGE TOLERANCE	24V± 3%	I/P:200VAC/240VAC O/P:full/min. load Ta:25 °C	±0.2%	P
LINE REGULATION	24V± 1%	I/P:200~240VAC O/P:full load Ta:25 °C	± 0.01%	P
LOAD REGULATION	24V± 2%	I/P:220VAC O/P:full~min. load Ta:25 °C	± 0.01%	P

SETUP TIME	3000ms/115VAC max. 1000ms/230VAC max.	I/P:115VAC I/P:230VAC O/P:full load Ta:25 °C	438ms/115VAC 176ms/230VAC	P
RISE TIME	100ms/115VAC max. 100ms/230VAC max.	I/P:115VAC I/P:230VAC O/P:full load Ta:25	11.46ms/115VAC 10.21ms/230VAC	P
HOLD UP TIME	10ms/115VAC typ. 50ms/230VAC typ.	I/P:115VAC I/P:230VAC O/P:full load Ta:25	10.4ms/115VAC 43.6ms/230VAC	P

1-3. PROTECTION FUNCTION TEST

TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
SHORT PROTECTION	short every output 1 hour no damage	I/P:277VAC O/P:full load Ta:25 °C	no damage, recovers automatically after fault removed	P
OVER LOAD PROTECTION	110% min.	I/P:115VAC I/P:230VAC O/P:testing Ta:25 °C	138%/115VAC 150%/230VAC recovers automatically after fault removed	P
OVER VOLTAGE PROTECTION	105~140%	I/P:115VAC I/P:230VAC O/P:min. load Ta:25 °C	134%/115VAC 134%/230VAC recovers automatically after fault removed	P

2. SAFETY TEST

TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
WITHSTAND VOLTAGE	I/P-O/P:3KVAC/1min<10mA	I/P-O/P:3KVAC/1min Ta:25 °C	I/P-O/P:1.7mA no damage	P
ISOLATION RESISTANCE	I/O-O/P:500VDC>100MΩ	I/P-O/P:500VDC Ta:25 °C	I/P-O/P:∞ no damage	P

3. RELIABILITY TEST

TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
LOW TEMP. TURN ON TEST	turn on after 2hour	I/P:220VAC O/P:full load Ta:-40°C	test ok	P
STORAGE TEMP. TEST	no damage	1.thermal shock temp.: -40~+75°C 2.test time low & high temp.:30min/each 3.total cycle:5cycle 4.input/output condition:static	test ok	P